



# George White & Co Pty Ltd - Catalogue

Australia's Leading Stockist of Non-Ferrous Metals



**Copper Tube: AS1432, 1571 & 1572**

**Round Tube:**



**C11000 - Electrolytic Tough Pitch**  
**C12200 - Phosphorous Deoxidised**

Continued...

Outside Diameter (mm)	Wall Thickness (mm)	Kg/Metre	Temper	AS Standard
3.18	0.56	0.041	ANN & HD & ACR	1572
3.97	0.56	0.065	ANN	1572
3.97	0.71	0.049	HD	1572
4.76	0.56	0.066	HD	1572
4.76	0.71	0.808	HD	1572
4.76	0.85	0.899	HD & HDR	1572
6.35	0.81	0.126	ANN	1571
6.35	0.91	0.098	ANN	1432
6.35	1.63	0.216	HD	KSD 5301
7.94	0.91	0.180	ANN	1432
9.53	0.71	0.176	HD	1432
9.53	0.81	0.198	HH / ACR	1571
<u>9.53</u>	<u>0.91</u>	<u>0.220</u>	<u>HD</u>	<u>1432 &amp; 1571</u>
9.53	1.63	0.362	HH	KSD 5301
12.70	0.81	0.270	HHR & ACR	1571
12.70	0.91	0.301	ANN & BQ	1432
12.70	1.02	0.335	BQ	1432
12.70	1.63	0.507	HH	KSD 5301
15.88	0.81	0.343	HH	1571
15.88	0.91	0.383	ACR, ANN & BQ	1432 & 1571
15.88	1.02	0.426	ANN, HHR & ACR	1432 & 1571
15.88	1.22	0.502	HD	1432
15.88	1.63	0.652	HH	1572
15.88	2.03	0.790	HD	1572
19.05	0.91	0.464	ANN & HHR	1432 & 1571
19.05	1.02	0.517	ANN, BQ & HHR	1432 & 1571
19.05	1.22	0.611	HD	1572

Outside Diameter (mm)	Wall Thickness (mm)	Kg/Metre	Temper	AS Standard
19.05	1.42	0.703	ANN & BQ	1432
19.05	1.63	0.797	HH & HD	1572
22.22	0.91	0.545	HHR	1571
22.22	1.22	0.720	HDR	1571
22.22	1.40	0.830	HDR	1571
25.40	0.91	0.626	HD & HDR	1432 & 1571
25.40	1.22	0.829	HD & HDR	1432 & 1571
25.40	1.63	1.088	HD	1432
25.40	3.25	2.022	HD	1572
28.58	0.91	0.707	HDR	1571
28.58	1.22	0.937	HDR	1571
31.75	0.91	0.806	HD & HDR	1432 & 1571
31.75	1.22	1.046	HD & HDR	1432 & 1571
<u>31.75</u>	<u>1.63</u>	<u>1.379</u>	<u>HD</u>	<u>1432</u>
31.75	2.03	1.694	HDR	1571
31.75	3.25	2.602	HD	1571
34.92	0.91	0.869	HDR	1571
34.92	1.22	1.155	HDR	1571
34.92	1.63	1.524	HD	1571
38.10	0.91	0.961	HD	1432
38.10	1.22	1.264	HD	1432
38.10	1.63	1.670	HD	1432
38.10	3.25	3.181	HD	1571
41.28	0.91	1.031	HDR	1571
41.28	1.22	1.372	HDR	1571

**Standard Length is 5.8 or 6.0 Metres for Straight Lengths**  
**Cutting Available for certain sizes P.O.A**

**Special Sizes/Alloys/Tempers can be Made to Order**

We can manufacture nearly any diameter or tolerance - All P.O.A

- Minimum Order Quantities will apply.
- Lead Times do apply.
- Other Alloys, Thickness' & Tempers can be Manufactured, please inform sales upon enquiry.
- Various Charges may apply.

**Temper Qualities:**

- ACR - Annealed Coils Refrigeration
- ANN - Annealed Coil
- BQ - Bending Quality
- HH - Half Hard Straight
- HHR - Half Hard Straight Refrigeration
- HD - Hard Drawn
- HDR - Hard Drawn Refrigeration Straight

Note: Weights are theoretical only.



# George White & Co Pty Ltd - Catalogue

Australia's Leading Stockist of Non-Ferrous Metals

Copper Tube: AS1432, 1571 & 1572

C11000 - Electrolytic Tough Pitch  
C12200 - Phosphorous Deoxidised



Round Tube:



Over 41.28mm

Outside Diameter (mm)	Wall Thickness (mm)	Kg/Metre	Temper	AS Standard
41.28	2.03	2.238	HD	1571
50.80	0.91	1.333	HD	1432
50.80	1.22	1.699	HD & HDR	1432 & 1571
50.80	1.63	2.250	HD	1432
63.50	0.91	1.599	HD	1432
63.50	1.22	2.134	HD	1432 & 1571
63.50	1.63	2.832	HD	1432
76.20	1.22	2.569	HD	1432
76.20	1.63	3.414	HD	1432 & 1571
76.20	2.03	4.229	HD	1432
101.60	1.22	3.440	HD	1432
101.60	1.63	4.577	HD	1432 & 1571
101.60	2.03	5.677	HD	1432
127.00	1.63	5.739	HD	1432
127.00	2.03	7.125	HD	1432
152.40	1.63	6.902	HD	1432
152.40	2.03	8.573	HD	1432
152.40	2.64	11.104	HD	1432
203.20	2.03	11.469	HD	1432
203.20	2.64	14.871	HD	1432

**Standard Length is 5.8 or 6.0 Metres for Straight Lengths  
Cutting Available for certain sizes P.O.A**

### Special Sizes/Alloys/Tempers can be Made to Order

We can manufacture nearly any diameter or tolerance - All P.O.A

- Minimum Order Quantities will apply.
- Lead Times do apply.
- Other Alloys, Thickness' & Tempers can be Manufactured, please inform sales upon enquiry.
- Various Charges may apply.

### Temper Qualities:

- ACR - Annealed Coils Refrigeration
- ANN - Annealed Coil
- BQ - Bending Quality
- HH - Half Hard Straight
- HHR - Half Hard Straight Refrigeration
- HD - Hard Drawn
- HDR - Hard Drawn Refrigeration Straight

Note: Weights are theoretical only.